

Rotor program

Fixed-angle rotors

All products consist of aluminium (black anodised).

Vessel			Rotor			
Nominal volume	Dimensions	Description Standard Features	Vessels per rotor	Rotors per unit	Part no. Configuration Setting angle (Reference: vertical)	
(ml)	Ø x length (mm)		(pcs.)	(pcs.)		
1.0	5 x 100 (vessel) 12.5 x 80 (cover)	round or flat bottom	72		112208¹⁾ adapter cover 30°	
1.5	11 – 12 x 31 – 39	round or flat bottom basic rotor for 126305	54	1 + 2	124534 massive rotor 25°	
1.5	11 – 12 x 31 – 39	round or flat bottom extension rotor for 124534	54	max. 2	126305 massive rotor 25°	
1.5 – 2.2	10.8 x 38	Eppendorf basic rotor for 126300	72	1 + 2	124532 massive rotor 45°	
1.5 – 2.2	10.8 x 38	Eppendorf extension rotor for 124532	72	max. 2	126300 massive rotor 45°	
2.5	10 x 40 – 50	basic rotor for 126307	54	1 + 2	112378 massive rotor 25°	

Rotor program

Vessel			Rotor			
Nominal volume	Dimensions	Description Standard Features	Vessels per rotor	Rotors per unit	Part no.	
(ml)	Ø x length (mm)		(pcs.)	(pcs.)	Configuration Setting angle (Reference: vertical)	
2,5	10 x 40 – 50	extension rotor for 112378	54	max. 2	126307 massive rotor 25°	
3.0 – 4.0	10 x 75 – 86	round or flat bottom	72		113312⁶⁾ adapter cover 20°	
5.0	15 x 50	flat bottom basic rotor for 126303	72	1 + 1	124515 disc rotor 30°	
5.0	15 x 50	flat bottom extension rotor for 124515	72	max. 1	126303 disc rotor 30°	
5.0	16.7 x 50.3 – 65	round or flat bottom basic rotor for 126304	36	1 + 2	124517 massive rotor 30°	
5.0	16.7 x 50.3 – 65	round or flat bottom extension rotor for 124517	36	max. 2	126304 massive rotor 30°	
5.0	14.5 – 15.5 x 45 – 51	basic rotor for 126308	40	1 + 2	124526 massive rotor 30°	
5.0	14.5 – 15.5 x 45 – 51	extension rotor for 124526	40	max. 2	126308 massive rotor 30°	

Vessel			Rotor			
Nominal volume	Dimensions	Description Standard Features	Vessels per rotor	Rotors per unit	Part no. Configuration Setting angle (Reference: vertical)	
(ml)	Ø x length (mm)		(pcs.)	(pcs.)		
5.0	12.5 – 13.8 x 70.4 – 86	round bottom, e.g. Sarstedt centrifuge tubes basic rotor for 126308	72	1 + 1	124527 disc rotor 20°	
5.0	12.5 – 13.8 x 70.4 – 86	round bottom, e.g. Sarstedt centrifuge tubes extension rotor for 124527	72	max. 1	126311 disc rotor 20°	
5.5	14.7 x 45	round or flat bottom	40	3	112228²⁾ massive rotor 30°	
5.0 / 7.0	12.5 x 75 – 85		72	1	124522 disc rotor 30°	
5.0 / 9.0	12 – 13 x 100 – 120	round bottom basic rotor for 126306	72	1 + 1	124524 disc rotor 30°	
5.0 / 9.0	12 – 13 x 100 – 120	round bottom extension rotor for 124524	72	max. 1	126306 disc rotor 30°	
8.0 / 10.0	12 – 13 x 100 - 120		54	1	124523 disc rotor 25°	

Rotor program

Vessel			Rotor			
Nominal volume	Dimensions	Description Standard Features	Vessels per rotor	Rotors per unit	Part no. Configuration Setting angle (Reference: vertical)	
(ml)	Ø x length (mm)		(pcs.)	(pcs.)		
10.0	16 – 17 x 65 – 100	basic rotor for 126302	48	1 + 1	124518³⁾ disc rotor 30°	
10.0	16 – 17 x 65 – 100	extension rotor for 124518	48	max. 1	126302 disc rotor 30°	
10.0	22.5 – 24 x 41 – 45	bottle, ISO 8362- 1 10R basic rotor for 126309	27	1 + 2	124530 massive rotor 25°	
10.0	22.5 – 24 x 41 – 45	bottle, ISO 8362- 1 10R extension rotor for 124530	27	max. 2	126309 massive rotor 25°	
10.0 12.0 15.0	16 – 16.5 x 80 – 125	round bottom, Falcon	48	1	124536 disc rotor (turn-over rotor) 20°	
12.0 to 15.0	19 x 80 and 19 x 100 – 125	round bottom	2 x 24	1	112294 disc rotor (combination rotor) 20°	
13.0	15.2 x 100 (vessel) 18 x 85 (cover)		48	--	110516⁴⁾ adapter cover	

Vessel			Rotor			
Nominal volume	Dimensions	Description Standard Features	Vessels per rotor	Rotors per unit	Part no. Configuration Setting angle (Reference: vertical)	
(ml)	Ø x length (mm)		(pcs.)	(pcs.)		
15.0	18 x 100 or 18 x 125		48	1	124538 disc rotor 20°	
21.0	15.6-16.5 x 104.3-162.5	e.g. Schott Duran (part no. 2613121)	48	1	124541 ³⁾ disc rotor	
22.0	20.1 X 76 (vessel) 27.5 x 60 (cover)	flat bottom and thread	24	1	112478 ³⁾⁷⁾ adapter cover	
30.0	18 X 180 (vessel) 21.5 x 146 (cover)	round bottom	24	1	112210 ⁵⁾ adapter cover	
30.0	24 – 25 x 105 – 120		18	1	124525 disc rotor 25°	
30.0 / 40.0	20 – 21.5 x 150 – 180		24	1	124528 disc rotor 20°	
30.0	27.5 x 72	flat bottom basic rotor for 112419	24	1 + 1	112418 ³⁾ disc rotor 22°	
30.0	27.5 x 72	flat bottom extension rotor for 112418	24	max. 1	112419 ³⁾ disc rotor 22°	
50.0	27 x 140		20	1	124539 ³⁾ disc rotor 22°	

Rotor program

Vessel			Rotor			
Nominal volume	Dimensions	Description Standard Features	Vessels per rotor	Rotors per unit	Part no. Configuration Setting angle (Reference: vertical)	
(ml)	Ø x length (mm)		(pcs.)	(pcs.)		
50.0	29.5 – 30 x 115 – 120	Falcon	18	1	124540 disc rotor 25°	
50.0	34.5 x 100 – 120		12	1	124544 disc rotor 28°	
100	45 x 100 – 120		8	1	124545 disc rotor 28°	
100	45 x 100 – 120		12	1	124547 disc rotor 23°	
150	58.6 – 61 x 110 – 120	flat bottom Falcon	6	1	124546 disc rotor 20°	
--		--	--	--	124533 distance ring	
--		--	--	--	112227²⁾ distance ring	

¹⁾ Only in conjunction with fixed-angle disc rotor, part no. 124522

²⁾ In order to use two rotors, a distance ring, part no. 110393, must be installed between the rotors.

³⁾ Delivery time on request, subject to technical relations.

⁴⁾ Only in conjunction with fixed-angle disc rotor, part no. 124538

⁵⁾ Only in conjunction with fixed-angle disc rotor, part no. 124528

⁶⁾ Only in conjunction with fixed-angle disc rotors, part no. 124527 and 126311

⁷⁾ Only in conjunction with fixed-angle disc rotors, part no. 112418 and 112419

Swing-out rotors

WARNUNG

The balance point of the loaded bucket must be located considerably below the pivotal point !

Plate		Rotor type and accessories			
Type	Dimensions	No. of plates per rotor	No. of plates per device	Part no.	
	B x T x H (mm)	(piece)	(piece)	Configuration Setting angle (Reference: vertical) Material	
MTP or DWP	max. 86.5 x 128.5 x 14.0 max. 86.5 x 128.5 x 53.0	6 2	12 4	124560	1 set, consisting of 2 rotors, no. 124511 1 coupling piece, no. 124553, 4 carriers, no. 141993 90° aluminium, black anodized
MTP or AP or DWP	max. 86.5 x 128.5 x 15.9 max. 86.5 x 128.5 x 25.9 max. 86.5 x 128.5 x 60.0	6 4 2	12 8 4	124567	1 set, consisting of 2 rotors, no. 124511 1 coupling piece, no. 124553, 4 carriers, no. 124708, 4 carrier plates, no. 124704 4 carrier plates, no. 124705 90° aluminium, black anodized
DWP	max. 86.5 x 128.5 x 60.0	2	4	124565	1 set, consisting of 2 rotors, no. 124511 1 coupling piece, no. 124553, 4 carriers, no. 124450 90° aluminium, black anodized and stainless steel, electropolished
				124511	Swing-out rotor for microtiter plates (MTP) assay plates (AP) and deepwell plates (DWP) 90° (swinging out fully) aluminium, black anodized

Rotor program

Plate		Rotor type and accessories			
Type	Dimensions	No. of plates per rotor	No. of plates per device	Part no.	
	B x T x H (mm)	(piece)	(piece)	Configuration	Setting angle (Reference: vertical)
				Material	
---	---	---	---	124553	
				Coupling piece, to connect two rotors no. 124511 aluminium, black anodized	
MTP oder DWP	max. 86.5 x 128.5 x 14.0	6	12	141993	
	max. 86.5 x 128.5 x 53.0	2	4	Carrier without bottom window, for 3 MTP or 1 DWP, suitable for rotor no. 124511 aluminium, black anodized	
MTP or AP or DWP	max. 86.5 x 128.5 x 15.9	6	12	124708	
	max. 86.5 x 128.5 x 25.9	4	8	Carrier, without bottom window, for 3 MTP or 2 AP or 1 DWP, suitable for rotor no. 124511 aluminium, black anodized	
	max. 86.5 x 128.5 x 60.0	2	4		
				124704	
				Carrier plate with distance piece, red, height 6 mm, suitable for carrier no. 124708 aluminium, black anodized	
				124705	
				Carrier plate with distance piece, blue, height 16 mm, suitable for carrier no. 124708 aluminium, black anodized	
DWP	max. 86.5 x 128.5 x 60.0	2	4	124450	
				Carrier, with bottom window, for 1 DWP, suitable for rotor no. Nr. 124511 stainless steel, electropolished	