

DIRECT-Q™ 3
DIRECT-Q 3 UV



Notice

The information in this document is subject to change without and should not be construed as a commitment by Millipore Corporation. Millipore Corporation assumes no responsibility for any errors that might appear in this document. This manual is believed to be complete and accurate at the time of publication. In no event shall Millipore Corporation be liable for incidental or consequential damages in connection with or arising from the use of this manual.

We manufacture and sell water purification systems designed to produce pure or ultrapure water with specific characteristics ($\mu\text{s/cm}$, T , TOC , CFU/ml , Eu/ml) when it leaves the water purification system provided that the Direct-Q System are fed with water quality within specifications, and properly maintained as required by the supplier.

We do not warrant these systems for any specific applications. It is up to the end user to determine if the quality of the water produced by our systems matches his expectations, fits with norms / legal requirements and to bear responsibility resulting from the usage of the water.

Copyright

2005 MILLIPORE CORPORATION. PRINTED IN KOREA. ALL RIGHTS RESERVED.

THIS BOOK OR PARTS THEREOF MAY NOT BE REPRODUCED IN ANY FORM WITHOUT THE WRITTEN PERMISSION OF THE PUBLISHERS.

FTPF09550

REV. 0 – 04/05

Millipore , Direct-Q , Millipak, Millex, BioPak , SmartPak DQ3 MILLIPORE

Tygon Norton Co

Velcro Velcro Industries

(Millipore Co.,Ltd.)

가

1

가

가


가

가

가

가

DECLARATION OF CONFORMITY
EUROPEAN UNION EC DIRECTIVE



Direct-Q

The Direct-Q System mentioned above is manufactured in Millipore SAS-67120 Molsheim – FRANCE – facilities whose quality management system is approved by an accredited registering body to the ISO9001 Quality System Standards.

We certify that these Lab Direct-Q Systems are designed and manufactured in application of the following European Council directives.

- 89/336/CEE relating to Electromagnetic compatibility
- 73/23/CEE relating to electrical equipment designed for use within certain voltage limits

Standards to which conformity is declared as applicable are the following :

- EN 61326-1 : 1997 : Electrical equipment for measurement , control and laboratory use-EMC requirements.
- EN 61010-1 : 2001 : Safety requirements for electrical equipment for measurement, control , and laboratory use .

Guy REYMANN

A handwritten signature in black ink, appearing to read "Guy Reymann", with a large, stylized initial "G" on the left.

Quality Assurance Manager

1	9
1-1	9
1-2	9
1-3	10
2	11
2-1	Direct-Q	11
2-2	Direct-Q 가	11
	11
	11
2-3	12
2-4	12
2-5	13
	13
3	14
3-1	14
	14
	14
	14
	15
3-2	15
	15
3-3	15
4	16
4-1	16
4-2	17

		17
	Reject	18
	Overflow	18
		19
4-3	–	20
		20
4-4	SmartPak	21
	SmartPak	21
	FLUSH	23
	SmartPak	23
4-5	Vent	24
4-6	Tygon	24
4-7		25
4-8		25
4-9	Final	26
4-10	DIRECT-Q	27
4-11		(C01).....	29
4-12	Setpoint	(C02).....	31
5	Direct-Q	33
5-1		33
5-2		33
		33
	RO	34
		35
5-3		37
	STANDBY.....		37
	FLUSH.....		37
	FILLING TANK.....		38
	PRE OPERATE.....		38
	DISPENSING.....		39

	AUTO-DISPENSING.....	39
5-4	FILLING TANK PRE OPERATE	40
5-5	FILLING TANK PRE OPERATE RO	40
5-6	41
5-7	42
	Pack	42
	UV	42
	FLUSH :	43
6	44
6-1	44
6-2	SmartPak	45
	SmartPak	45
	SmartPak	46
	FLUSH	47
	SmartPak	47
	Vent	48
	Tygon	48
	48
	48
	Final	48
6-3	Final	49
6-4	50
6-5	(C04).....	51
6-6	(C03).....	53
6-7	55
	55
	,	56
6-8	58

		58
		59
6-9	UV (UV).....		61
	UV		62
	UV		63
6-10	UV (C05).....		64
	UV		64
	UV		65
7		66
8		66
8-1	Direct-Q		66
8-2		66
8-3		66

1

1-1

Direct-Q 3 , Direct-Q 3 UV

1-2

Direct-Q



HAZARD



ATTENTION


가



UV RADIATION



DANGER



ELECTRICAL GROUND

가



ELECTRICAL DANGER

1-3

Millipore

Millipore

: 02-3011-9600

Fax : 02-564-2077

: 042-487-6116

,

Internet Site Address : www.millipore.com


www.millipore.com/techservice

Email : H2O@millipore.com

(가 ,)

2

2-1 Direct-Q




2-2 Direct-Q 가

RO			(5 < T < 35)
25	3L ± 15%	42L	30L

Resistivity ()	18.2MΩ.cm @ 25
Conductivity ()	0.056μs/cm @ 25
Total Organic Carbon (TOC)	10 μg / L (ppb) (UV) 30 μg / L (ppb) (UV)
Micro - Organisms	1 CFU / ml (Millipak Filter)

2-3




1		8	6
2		9	
3	SmartPak DQ3 (Pretreatment and RO Cartridge)	10	UV 185 nm (UV)
4	RO	11	SmartPak DQ3 (Ion Exchange Polisher Cartridge)
5	RO	12	
6		13	Point-of-Use (POU)
7	RO	14	Final

2-4

SmartPck DQ3 . Smartpak DQ3 (“Smartpak”) 3
 가 가 .
 (RO) membrane , Ion Exchange resin
 . SmartPak .
 fouling chlorine oxidation RO membrane
 RO membrane . RO 6 .
 RO Ion Exchange Polisher . RO membrane
 , , , Reject .
 Dispensing , 가 가 , RO UV . UV
 185nm 254nm . UV . UV
 . UV Exchange Polisher
 가 . Final
 . Final .

2-5



가 : 56 cm
 : 42 cm
 : 64 cm

	Direct-Q 3	Direct-Q 3 UV
	17.6 kg	18.2 kg
	8.1 kg	8.6 kg
	13.4 kg	13.9 kg

Noise

Direct-Q 1 36dB 가 .

100 VAC ± 10% 50/60 Hz. 0.68 amp source , 2amp T(Time Lag) fuse , Power = 100VA

120 VAC ± 10% 50/60 Hz. 0.68 amp source , 2amp T fuse , Power = 100VA

230 VAC ± 10% 50/60 Hz. 0.68 amp source , 2amp T fuse , Power = 100VA



2.5

3

3-1

	40 L
	0.5 bar
	6 bar
	2000 $\mu\text{s} / \text{cm}$
	5 ~ 35
PH	4~ 10
Fouling Index	10
	0.1 ppm as CaCO ₃
	0.05 ppm as CaCO ₃
	0.05 ppm as CaCO ₃
Free Chlorine	1 ppm
Langelier Saturation Index	+ 0.2
TOC	2000 ppb

	1/2 inch Male GAZ , NPTM or BSPM
--	----------------------------------

	30 L
--	------

	5 < T < 40
	5 < T < 40
	31 : 80%
	31 ~ 40 : 50% ~ 80%
	3000 m
Installation Category	II
	2

3-2

가 가

Connector

Connector Kit TANKPECKT 6 30
Connector Kit 30
. 30 PE
TANKPE030

3-3

Direct-Q

4

4-1

(A)

(B)

(C) UV

A



B



C



4-2


Direct-Q (A)

A

1

2

Reject



3

Overflow

4

(B)

GAZ

1/2

GAZ

가 1/2

(C)

B



C



Reject

(D)

Reject



D

Reject

Overflow

(E)

Overflow



E

Overflow

F, G, H

(I)

SmartPak flush

F



G



H



I



4-3


(A) 가 STANDBY

가

(B)

, STANDBY

가




A



B

C



4-4 SMARTPAK



SMARTPAK
SMARTPAK

SMARTPAK UV

SmartPak

가 . STANDBY

SmartPak


SmartPak

(C) O-



A

B



C



D , E , F

SmartPak

NOTE : (G)



D



E



F



FIUSH



FLUSH

(H) 15 FLUSH

FLUSH 가 , FILLING
TANK

H




SmartPak

15

FILLING TANK
SmartPak

I



가

가

1 30 2

가

(5-1)

J

Vent

(4-5)



4-5 Vent

Vent

(A) , (B)

Vent

A



B



4-6 Tygon

Tygon

(C) POU



POU

POU

O-

(D)

Tygon

C



D



4-7

Smartpak , Tygon
Smartpak

(A) RO 가 가

(B)
Dispensing

(C) 가 60% FILLING
TANK

4-8


Final
FILLING TANK PRE-OPERATE
(5-4)
, SmartPak
STANDBY

1

Tygon POU

Final
(4-9)
4-9 Final


A



B



C



Final Millipak Express 20 BioPak Ultrafiltration 2 가
 POU Tygon
 (A) POU Final . Final



. POU
 O-

. DISPENSING
 (B) (Final 가 Millipak) Millipak


Millipak



Millipak membrane
 가 Millipak

1 가

FILLING TANK





Final Tygon
 . (가 Tygon



1 “Main” , “ – “
“F01” 가









2 “Main”
“F02” 60



3
60 가









NOTE : 60 가 가 10% ,



<p>4 1</p>		
<p>5 “+” “-”</p>		
<p>6 “Main” 2 가 “Main”</p>		

가 .



가 25

<p>1 “Main”, “+” “C01” 가 (MΩ. Cm @ 25)</p>		
<p>2 “+” “-” (MΩ. cm)</p>		
<p>3 “+” “-” (μS/ cm @ 25)</p>		

4 “+” “-“
($\mu\text{S/cm}$)

5 “Main” 2
가
“Main”





Setpoint



(5-7

) 5MΩ. Cm @ 25


1 “Main” “+”
“C01” 가



2 “Main”
C02 Setpoint



3 “+” ”-“
Setpoint
1.0MΩ.cm@25 ~18.0
MΩ.cm@25 가



C01 0.999 μs/cm @25 ~ 0.055 μs/cm @25

Setpoint

NOTE :

0.001



“055 μs/cm @25 ”

, “055 X 0.001 = 0.055 “

“ 0.055 μs/cm @25 ”


4 "Main" 2

가
"Main"




5 Direct-Q

5-1



5-2

2가



가 10%

가 10%가

RO


RO 가

RO





(F01)

1 “Main” “ - “
 . “F01”
 가 .




2
 “+” , “-“
 . 0.25 ~ 9.75 L
 0.25L
 가 .





NOTE : 4-10

가 .

3



NOTE :

<p>4 “Main” 2</p> <p>가</p> <p>“Main”</p>		
--	---	---

5-3

STANDBY

STANDBY 가
STANDBY 가 10

A rectangular graphic with a dark grey background and the word "STANDBY" in bright yellow, bold, sans-serif capital letters.

. STANDBY

FLUSH

SmartPak ,
FLU 15가 . FLUSH


SmartPak
SmartPak
FLUSH

FLUSH

FLUSH


FLUSH
,FLUSH가

TANK FULL 24 FAST FLUSH
2



FILLING TANK

FILLING TANK 100%
 RO
 FILLING TANK 60%
 FLUSH 가



FILLING TANK


10% , FILLING TANK



FILLING TANK

PRE OPERATE

, FILLING TANK
 PRE-OPERATE 가
 60% ~ TANK FULL



PRE OPERATE 2 3
 가

3



10

DISPENSING

DISPENSING

DISPENSING 가 , 가
가 .




10





AUTO-DISPENSING

AUTO-DISPENSING “ F01 “
. AUTO-DISPENSING
pre-set 가 .
가
가 10



5-4 FILLING TANK PRE OPERATE




NOTE : DISPENSING

5-5 FILLING TANK

PRE OPERATE

RO




NOTE : $\mu\text{s/cm}$

5-6

3

2


3



NOTE :

5-7

Pack



, SmartPak



, SmartPak

Setpoint

Setpoint

C02




가 , SmartPak

, SmartPak

Millipore

UV



UV

, UV

UV

가 UV


0 day

UV

C05

. UV

UV



UV

가

, UV

가

, UV

Millipore

FLUSH :






FLUSH

FLU


가

FLUSH

6-1

SmartPak	<p>가</p>  <p>가</p> 	6-2
Final	SmartPak ,	6-3
Vent	SmartPck	4-5
	Final ,	4-10
		6-5
UV UV	<p>UV 가</p> 	6-9 , 6-10
	1 2	6-4
	1 1 . SmartPak	6-7 , 6-7
	1 1	6-5

6-2 SmartPak



SmartPak

STANDBY

10 STANDBY 가

Final

(A) 가

(B)

(C)

SmartPak

SmartPak

SmartPak

UV

A



B



C



SmartPak

SmartPak

SmartPak

O-

D,E,F

D



E



F



NOTE :

(G)



G

FLUSH



(H) 15 FLUSH

SmartPak

(I) FLUSH 가
FILLING TANK

SmartPak


15 FILLING TANK

SmartPak 가

(J)

1 30
2 가
가 100%

H



I

J



Vent

SmartPak Vent

K



(K) Vent

(4-5) Vent

Tygon

(M)

M

Tygon (4-6)



4-7

(N) (4-8)

Final

(O) (6-3)

N



O



6-3 Final

SmartPak

Final

Final 가

Final



SmartPak


Final

(A)

Final

POU

Final



POU

O-

(B) (


Final

가

Millipak

) Millipak

Millipak



Millipak membrane

가 Millipak

1

가

FILLING TANK

A



B



Final

(4-10)

6-4

가

1 2

STANDBY

8 mm OD

(A)

(B)

(C)

PRE OPERATE

A



B




C





6-5

(C04)


1 “Main” , “ + “
“ C01” 가



2 “Main” 3
C04
가
가



3 “+” , “-“
가
가 가



NOTE : 가 가

4



NOTE : 10% 가



5



6 “+” , “-“
가

FILLING

TANK



NOTE : 가

100%


POU

Final



Tygon

Tygon



1 “Main” , “ + “
가 “C01”



2 “Main” 2
C03




3 “+” , “-“
POU



NOTE :

4

FILLING TANK





Hydrogen Peroxide

(A) 50%

(B)

30% Hydrogen Peroxide 200ml Peroxid

200ml


Millipore

Hydrogen

SmartPak


SmartPak, Final

, Vent



4 50

A



B



(C) (STANDBY)

(D) Vent

(E)

(F) Hydrogen peroxide (30%) 200ml (1ml = 1 cc)

200ml 가 air vent


(G)

FILLING TANK

가

100%

(H)



(I) (1) Final
(J)

Tygon
EMPTY TANK(C03)

(K) 가 ,
100%

FILLING TANK

(L)

EMPTY TANK(C03)


(M)
SmartPak , Vent , Final

(STANDBY)


I




J



K



L



M





Hydrogen Peroxide

가

(A) 50%

(B)


30% Hydrogen Peroxide 200ml Peroxid

200ml


Millipore

Hydrogen

Vent



4 50



A



B

(C)

(STANDBY)

(D) Vent

(E)

(F) Hydrogen peroxide (30%) 200ml (1ml = 1 cc)

200ml 가 air vent


(G)

FILLING TANK

가

100%

(H)



(I) 가 , 1

(STANDBY)

(J) 1

(K)

(L)

100%

FILLING TANK



I,J,K,L

(I)

(STANDBY)

(J)

(K)

(L)

FILLING TANK

6-9 UV

(UV

)

UV

UV

UV

가 0 day

. 6-10

(A) (STANDBY)
(B) ,



. UV

Final

(C) SmartPak

A



B



C



UV

UV

Velcro®

(D) UV

NOTE : UV

(E) UV

(F) UV



UV
UV

D



E



F



UV

(G) UV
UV

(H) UV

(I) Velcro®

(J) SmartPak



SmartPck
SmartPak

15

FLUSH

UV (6-10)

G



H



I



J



6-10 UV

(C05)

UV

UV

. UV







UV

UV







가 0 day
, UV

UV
가

UV



<p>1 “Main” , “+” “C01” 가</p>		
<p>2 “Main” 4 C05 , UV</p>		
<p>3 2 “Main” “Main”</p>		

UV





<p>1 “Main” , “+” 가 . “C01”</p>		
<p>2 “Main” 3 . C04 , UV 0 days</p>		
<p>3 “+” , “-“ . 500 days UV</p>		

UV

LCD	가 . 가
FILLING TANK 가 가	가 가 RO Membrane	. . (6-5) SmartPak .
가	10% . 가 . Millipak 가 . Final 가 .	FILLING TANK . . Millipak Final . (6-3)
가 10% DISPENSING	가 . DISPENSING	. (6-5)


<p>AUTO-DISPENSING 가</p>	<p>Final 가 가 Final 가</p>	<p>(4-10) Final Final</p>
<p>“+” RO 가</p>	<p>FILLING TANK</p>	<p>RO TANK FILLING</p>
<p>FILLING TANK PRE OPERATE “-“</p>	<p>DISPENSING</p>	
	<p>가 FLUSH</p>	
	<p>SmartPak Setpoint</p>	<p>SmartPak (6-2)</p>

--	--	--

	<p>SmartPak</p>	<p>SmartPak SmartPak Pack Millipore</p>
	<p>Setpoint STANDBY</p>	<p>SmartPak (6-2) (5-6)</p>
 <p>UV</p>	<p>UV</p>	<p>UV (6-9) UV UV (6-10)</p>
 <p>UV</p>	<p>UV 가</p>	<p>UV UV UV Millipore</p>

8-1 DIRECT-Q

100VAC , 120 VAC , 230 VAC



8-2

SmartPak DQ3	SPR00SIA1
Millipak Express 20 (Non - Sterile) – 1/box	MPGP02001
BioPak Ultrafiltration	CDUFBI001
Millex Vent (1 μm) , 2/box	TANKMPK03
UV 185 nm	SYN185UV1
	SANIKIT01

8-3

	WMBSMT002
	TANKPECKT
30 PE	TANKPE030